

CA515R



HEAT-RESISTANT COWHIDE WELDER'S GLOVE

Ref. CA515R



#### Product specifications

Heat-resistant cowhide split leather (HR). Hand with cotton fleece lining. Cuff with canvas lining. American assembly. Length: 35 cm.

Heat-resistant leather, thickness: 1.2mm to 1.4mm.

Lined hand : swansdown.

Lined cuff : cotton cloth 300 g/m<sup>2</sup>.

#### COLOUR

Red

#### SIZE

10

#### Product Use - Risks



Heat



Wearing



Heavy industry

## Certifications and Standards



DIRECTIVE EPI 89/686/CEE

### EN420:2003 General requirements

4: Dexterity



### EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)

3: Resistance to abrasion (from 0 to 4)  
1: Resistance to cut (from 0 to 5)  
3: Resistance to tear (from 0 to 4)  
3: Resistance to perforation (from 0 to 4)



### EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

4: Resistance to flammability (from 1 to 4)  
1: Resistance to contact heat (from 1 to 4)  
3: Resistance to convective heat (from 1 to 4)  
x: Resistance to radiant heat (from 1 to 4)  
4: Resistance to small projections of molten metal (from 1 to 4)  
x: Resistance to large projections of molten metal (from 1 to 4)

### EN12477:2001/A1:2005 Protective gloves for welders

A: Welding - Other welding processes - less dexterity - Type A

## References

References	Bar code	COLOUR	SIZE		
CA515R10	3295249025939	Red	10	60	12