

# AXIS 2



1654101 • Clear Lens



1654102 • Smoke Lens



1654118 • Contrast Lens



Tilt Adjustable Arms



28 g

**+ HIGH CONTOUR (10.5 BASE), DISTORTION FREE**

**SINGLE PIECE LENS**







**+ TILT ADJUSTABLE, CO-MOULDLED TEMPLE ARMS**

**FOR CUSTOMISED SECURE FIT PROTECTION**

**AGAINST DUST AND OTHER PARTICLES**

**bollé**  
SAFETY

# AXIS 2

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
<b>AXIS 2</b>	 Clear	1654101	IO & 	AS/NZS 1337.1.2010	AF / AS
	 Smoke	1654102	I3 & 	AS/NZS 1337.1.2010	AF / AS
	 Contrast	1654118	IO & 	AS/NZS 1337.1.2010	Hard Coat

## LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

 Manufacturer name

## OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear & contrast).
- 3. Range of luminous transmittance 8 -18% (smoke).

## APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory
- Dental


## MAIN MARKETS

- Manufacturing
- Local government and councils
- Utilities: power, gas, water and roads
- Medical and dental
- Transport
- Mining
- Construction

## LENSES

- 2mm polycarbonate
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear and Smoke
- Hard coating on Contrast lens
- 100% UV 385 – Clear
- 100% UV 400 – Smoke and Contrast

## CLEANING AND STORAGE

**CLEANING :** Bollé Safety recommends only using our  Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

## FRAME MARKING

**AS/NZS 1337.1.2010 :** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

## ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

## NEW ZEALAND:

Bollé New Zealand Limited  
Unit 5, 114 Sawyers Arms Road  
Papanui, Christchurch 8052  
T: 03 3751400  
E: bolle@bolle.co.nz

[bollesafety.com.au](http://bollesafety.com.au)

**bolle**  
SAFETY