

730 Nitri-Solve



Unsupported, coton flock Nitrile coating

DESCRIPTION

- Fully coated
- Scalloped edge
- Textured finish
- Without special treatment
- Anatomical shape
- Does not contain silicones



BENEFITS

- A flexible glove that absorbs perspiration
- Protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip
- Impermeable for working in damp or greasy environments
- Surface provides better grip
- Minimal allergy risks
- Designed for easy movement and continuous wear
- Can easily be one-hand used
- Wrist well protected

RECOMMENDED FOR THESE RISKS:

Chemical protection

RECOMMENDED FOR THESE LINES OF WORK:

Automotive
Chemical
Metallurgy
Public sector

AVAILABLE SIZES

7 • 8 • 9 • 10 • 11

LENGTH

Dependent on size, in mm (flat)

330

PACKAGING

Pairs per pack/box

6/72

COLOUR OF SUPPORT/COATING

Green

THICKNESS

in mm

0,38

RECOMMENDATIONS FOR USE

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- Potential allergens: thiazole

89/686/CEE Cat. III	EN 388 - 2003	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	EN 374-2 - 2003	EN 374-3 - 2003	J - N-HEPTANE 0 1 2 3 4 5 6	K - CAUSTIC SODA 40% 0 1 2 3 4 5 6
0321	1101	TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4			L - SULPHURIC ACID 96 0 1 2 3 4 5 6	
					JKL		

EC compliance certificate delivered by the notified body 0321
SATRA House - Rockingham Road, Kettering - Northamptonshire NN16 9JH - United Kingdom

[Updated 11/06/14]

SHOWA BEST GLOVE

Tour Franklin - La Défense 8 - 92042 Paris La Défense Cedex - France
Tel. +33 (0)1 55 62 14 20 - Fax +33 (0)1 55 62 14 29
info@showabestglove.eu - www.showabestglove.eu

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

